

### 產品特點

1. 簡易且快速安裝的PU聚氨酯同步帶。
2. 可使用於正反轉輸送設備上。
3. 可使用於惰輪與背膠加工的同步帶。
4. 保持與同步帶相同的帶輪直徑要求。
5. 可以提供多種齒型的應用設計！
6. 沒有間隙！運轉精準！低噪音！

### PRODUCT CHARACTERISTICS

1. Easy and quick installation.
2. Can be used in forward and reverse conveyor.
3. Can be used in idler pulleys and timing belt with back face machining conveying materials.
4. Keep the same pulley diameter requirements as the timing belt.
5. Provide various tooth type applied design!
6. No gap! Operation precisely! Low noise!



皮帶規格 Belt Type	齒距 (in/mm) Pitch	最小皮帶寬 (in/mm) Minimum Belt Width	最大皮帶寬 (in/mm) Maximum Belt Width
T5	5	10	50
T10	10	16	100
T20	20	25	100
AT5	5	10	50
AT10	10	16	100
AT20	20	25	100
HTD5M	5	10	100
HTD8M	8	15	100
HTD14M	14	40	100
STD5M	5	10	100
STD8M	8	15	100
STD14M	14	40	100
RPP5M	5	10	100
RPP8M	8	15	100
RPP14M	14	40	100
L	3/8" / 9.525	1/2" / 12.7	4" / 101.6
H	1/2" / 12.7	1/2" / 12.7	4" / 101.6