

車削型

Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring


NKI
NKIS
NA 49
NA 59
NA 69




NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)




NA 69 (F≥40)



NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single row



NA 69 (F≥40)
double row



軸徑 Shaft dia.	軸承型號 Series					單位重 Weight
	NKI	NKIS	NA 49	NA 59	NA 69	
mm	NKI	NKIS	NA 49	NA 59	NA 69	g
9	NKI 9/12					16.7
	NKI 9/16					22.5
10			NA 4900			24
	NKI 10/16					30
	NKI 10/20					38
12			NA 4901			26.5
	NKI 12/16					33.5
	NKI 12/20					42.5
					NA 6901	44.5
15	NKI 15/16					39.5
	NKI 15/20					50
			NA 4902			35
				NA 5902		52
					NA 6902	61

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
9	12	19	12	0.3	1.5	640	690	26000
9	12	19	16	0.3	2	880	1040	26000
10	14	22	13	0.3	0.5	960	1050	24000
10	14	22	16	0.3	0.5	1130	1290	24000
10	14	22	20	0.3	0.5	1430	1750	24000
12	16	24	13	0.3	0.5	1000	1160	23000
12	16	24	16	0.3	0.5	1250	1540	23000
12	16	24	20	0.3	0.5	1580	2080	23000
12	16	24	22	0.3	0.5	1740	2370	23000
15	19	27	16	0.3	0.5	1420	1910	21000
15	19	27	20	0.3	0.5	1790	2580	21000
15	20	28	13	0.3	0.5	1130	1440	20000
15	20	28	18	0.3	1	1620	2290	20000
15	20	28	23	0.3	1	1970	2950	20000

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型

Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI

NKIS




NA 49

NA 59

NA 69

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight
	NKI	NKIS	NA 49	NA 59	NA 69	
mm	NKI	NKIS	NA 49	NA 59	NA 69	g
17	NKI 17/16					43.5
	NKI 17/20					54
			NA 4903			39
				NA 5903		56
					NA 6903	67
		NKIS 17				98
20	NKI 20/16					48.5
	NKI 20/20					61
			NA 4904			78.5
				NA 5904		115
					NA 6904	136
		NKIS 20				129

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
17	21	29	16	0.3	0.5	1460	2040	19000
17	21	29	20	0.3	0.5	1840	2760	19000
17	22	30	13	0.3	0.5	1220	1630	18000
17	22	30	18	0.3	1	1640	2400	18000
17	22	30	23	0.3	1	2120	3340	18000
17	24	37	20	0.6	1	2640	3300	17000
20	24	32	16	0.3	0.5	1550	2300	17000
20	24	32	20	0.3	0.5	1960	3110	17000
20	25	37	17	0.3	0.8	2210	2670	16000
20	25	37	23	0.3	1	3050	4050	16000
20	25	37	30	0.3	1	3820	5400	16000
20	28	42	20	0.6	0.5	2970	3730	14000

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型

Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring


NKI
NKIS
NA 49
NA 59
NA 69




NKI, NKIS, NA49
NA 59, NA 69(F≤35)




NA 69 (F≥40)



NKI, NKIS, NA49
NA 59, NA 69(F≤35)
single row



NA 69 (F≥40)
double row



軸徑 Shaft dia.	軸承型號 Series					單位重 Weight	
	mm	NKI	NKIS	NA 49	NA 59		NA 69
22		NKI 22/16					52
		NKI 22/20					67.5
				NA 49/22			87
					NA 59/22		134
						NA 69/22	152
25		NKI 25/20					82
		NKI 25/30					123
				NA 4905			92.5
					NA 5905		139
						NA 6905	160
			NKIS 25				162

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r min.	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
22	26	34	16	0.3	0.5	1630	2550	15000
22	26	34	20	0.3	0.5	2070	3450	15000
22	28	39	17	0.3	0.8	2270	3090	15000
22	28	39	23	0.3	1	2960	4380	14000
22	28	39	30	0.3	1	3380	5180	14000
25	29	38	20	0.3	1	2150	3790	14000
25	29	38	30	0.3	1.5	3080	6030	14000
25	30	42	17	0.3	0.8	2510	3310	13000
25	30	42	23	0.3	1	3300	4700	13000
25	30	42	30	0.3	1	3740	5550	13000
25	32	47	22	0.6	1	3680	4750	13000

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型




Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI
NKIS
NA 49
NA 59
NA 69NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight
	NKI	NKIS	NA 49	NA 59	NA 69	
mm						g
28	NKI 28/20					96.5
	NKI 28/30					145
			NA 49/28			101
				NA 59/28		142
					NA 69/28	176
30	NKI 30/20					112
	NKI 30/30					171
			NA 4906			106
				NA 5906		152
					NA 6906	184
		NKIS 30				184

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r min.	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
28	32	42	20	0.3	1	2510	4150	13000
28	32	42	30	0.3	1.5	3600	6580	13000
28	32	45	17	0.3	0.8	2610	3530	13000
28	32	45	23	0.3	1	3420	5010	13000
28	32	45	30	0.3	1	3910	5920	13000
30	35	45	20	0.3	0.5	2540	4370	11000
30	35	45	30	0.3	1	3630	6930	11000
30	35	47	17	0.3	0.8	2680	3770	11000
30	35	47	23	0.3	1	3520	5340	11000
30	35	47	30	0.3	1	4370	7060	11000
30	37	52	22	0.6	1	4140	5800	11000

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型




Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI
NKIS
NA 49
NA 59
NA 69NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight	
	mm	NKI	NKIS	NA 49	NA 59		NA 69
32	NKI 32/20						121
	NKI 32/30						180
				NA 49/32			165
					NA 59/32		241
						NA 69/32	295
35	NKI 35/20						129
	NKI 35/30						192
				NA 4907			178
					NA 5907		256
						NA 6907	320
			NKIS 35				220
38	NKI 38/20						136
	NKI 38/30						205

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r min.	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
32	37	47	20	0.3	0.5	2620	4580	11000
32	37	47	30	0.3	1	3750	7270	11000
32	40	52	20	0.6	0.8	3130	4780	10000
32	40	52	27	0.6	1	4040	6620	10000
32	40	52	36	0.6	0.5	5370	9550	10000
35	40	50	20	0.3	0.5	2700	4980	10000
35	40	50	30	0.3	1	3870	7920	10000
35	42	55	20	0.6	0.8	3180	5020	9500
35	42	55	27	0.6	0.8	4580	7550	9500
35	42	55	36	0.6	0.5	5270	9600	9500
35	43	58	22	0.6	0.5	4200	6150	9500
38	43	53	20	0.3	0.5	2780	5200	9500
38	43	53	30	0.3	1	4090	8570	9500

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型




Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI
NKIS
NA 49
NA 59
NA 69NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight
	NKI	NKIS	NA 49	NA 59	NA 69	
mm	NKI	NKIS	NA 49	NA 59	NA 69	g
40	NKI 40/20					143
	NKI 40/30					215
			NA 4908			245
				NA 5908		348
					NA 6908	440
		NKIS 40				281
42	NKI 42/20					149
	NKI 42/30					225
45	NKI 45/25					230
	NKI 45/35					320
			NA 4909			285
				NA 5909		396
					NA 6909	520
		NKIS 45				336

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
40	45	55	20	0.3	0.5	3150	6180	9000
40	45	55	30	0.3	1	4200	8900	9000
40	48	62	22	0.6	1	4150	6780	8500
40	48	62	30	0.6	0.5	5800	10340	8500
40	48	62	40	0.6	0.5	6320	11600	8500
40	50	65	22	1	0.5	4590	7180	8000
42	47	57	20	0.3	0.5	3230	6390	8500
42	47	57	30	0.3	1	4630	10200	8500
45	50	62	25	0.6	1.5	4140	8200	8000
45	50	62	35	0.6	2	5700	12400	8000
45	52	68	22	0.6	1	4170	7110	7500
45	52	68	30	0.6	1	6080	11280	7500
45	52	68	40	0.6	0.5	6790	13300	7500
45	55	72	22	1	0.5	5160	8050	7500

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型

Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI

NKIS




NA 49

NA 59

NA 69

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight	
	mm	NKI	NKIS	NA 49	NA 59		NA 69
50	NKI 50/25					270	
	NKI 50/35					365	
				NA 4910		295	
					NA 5910	498	
						NA 6910	530
			NKIS 50				518
55	NKI 55/25					275	
	NKI 55/35					385	
				NA 4911		410	
					NA 5911	559	
						NA 6911	730
			NKIS 55				558

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r min.	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
50	55	68	25	0.6	0.5	4200	8840	7500
50	55	68	35	0.6	2	5770	13300	7500
50	58	72	22	0.6	1	4590	8130	7000
50	58	72	30	0.6	1	6340	12200	7000
50	58	72	40	0.6	0.5	7520	15200	7000
50	60	80	28	1.1	2	6950	11400	6500
55	60	72	25	0.6	1.5	4790	10600	6500
55	60	72	35	0.6	2	6590	16000	6500
55	63	80	25	1	1.5	6010	10200	6500
55	63	80	34	1	1.5	8290	15500	6500
55	63	80	45	1	1.5	9890	19400	6500
55	65	85	28	1.1	2	7040	12000	6000

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型




Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI
NKIS
NA 49
NA 59
NA 69NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight	
	mm	NKI	NKIS	NA 49	NA 59		NA 69
60		NKI 60/25					395
		NKI 60/35					560
				NA 4912			440
					NA 5912		614
						NA 6912	785
			NKIS 60				560
65				NA 4913			470
					NA 5913		655
						NA 6913	840
		NKI 65/25					470
		NKI 65/35					710
			NKIS 65				641

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r min.	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
60	68	82	25	0.6	1	5530	12100	6000
60	68	82	35	0.6	1	7650	18400	6000
60	68	85	25	1	1.5	6120	10700	6000
60	68	85	34	1	1.5	8420	16200	6000
60	68	85	45	1	1.5	10100	20900	6000
60	70	90	28	1.1	2	6750	12400	5500
65	72	90	25	1	1.5	6750	11700	5500
65	72	90	34	1	1.5	9280	17700	5500
65	72	90	45	1	1.5	10800	21900	5500
65	73	90	25	1	1	6150	13200	5500
65	73	90	35	1	1	8510	20100	5500
65	75	95	28	1.1	2	7710	14200	5500

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型




Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI
NKIS
NA 49
NA 59
NA 69NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight
	NKI	NKIS	NA 49	NA 59	NA 69	
mm	NKI	NKIS	NA 49	NA 59	NA 69	g
70	NKI 70/25					540
	NKI 70/35					755
		NKIS 70				737
			NA 4914			765
				NA 5914		1010
					NA 6914	1400
75	NKI 75/25					675
			NA 4915			810
	NKI 75/35					945
					NA 6915	1480
80	NKI 80/25					710
			NA 4916			855
	NKI 80/35					995
					NA 6916	1560

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r min.	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
70	80	95	25	1	0.8	6530	14400	5000
70	80	95	35	1	0.8	9030	21900	5000
70	80	100	28	1.1	2	7880	15300	5000
70	80	100	30	1	1.5	9120	16800	5000
70	80	100	40	1	1.5	12100	24200	5000
70	80	100	54	1	1	14400	30700	5000
75	85	105	25	1	1	7770	15100	4700
75	85	105	30	1	1.5	10200	19800	4700
75	85	105	35	1	1	10700	22900	4700
75	85	105	54	1	1	15200	33000	4700
80	90	110	25	1	1	8140	16100	4400
80	90	110	30	1	1.5	10100	20500	4400
80	90	110	35	1	1	9740	20300	4400
80	90	110	54	1	1	15100	34300	4400

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.

車削型




Needle Roller Bearings

標準式_有內輪

With ribs-with inner ring

NKI
NKIS
NA 49
NA 59
NA 69NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)

NA 69 (F≥40)

NKI ,NKIS, NA49
NA 59 ,NA 69(F≤35)
single rowNA 69 (F≥40)
double row

軸徑 Shaft dia.	軸承型號 Series					單位重 Weight
	NKI	NKIS	NA 49	NA 59	NA 69	
mm	NKI	NKIS	NA 49	NA 59	NA 69	g
85	NKI 85/26					775
	NKI 85/36					1080
			NA 4917			1280
					NA 6917	2340
90	NKI 90/26					820
	NKI 90/36					1140
			NA 4918			1350
					NA 6918	2460
95	NKI 95/26					860
	NKI 95/36					1190
			NA 4919			1420
					NA 6919	2580

(1)除了標準的型號之外,SYI亦接受訂製特殊的尺寸規格,特殊型號標示為NKI dr x D x B例如NKI 15x33x12.
Other than the series shown above, custom-made orders are available according to the series number NKI dr x D x B.

(2)當使用油脂潤滑時,極限回轉速為表列數值的60%.
With grease lubrication, 60% of the values given in the tables are permissible.

尺寸 Dimensions mm						基本額定負荷 Basic load ratings		極限回轉速 Limited Speed
d	F	D	B	r	S	動 Dynamic C kgf	靜 Static Co kgf	機油潤滑 Oil rpm (2)
85	95	115	26	1	1.5	8200	17100	4200
85	95	115	36	1	1.5	11300	26000	4200
85	100	120	35	1.1	1	9070	18000	4000
85	100	120	63	1.1	1	18000	43400	4000
90	100	120	26	1	1.5	8550	18100	4000
90	100	120	36	1	1.5	11800	27600	4000
90	105	125	35	1.1	1	12600	29000	3800
90	105	125	63	1.1	1	18100	46100	3800
95	105	125	26	1	1.5	8890	19200	3800
95	105	125	36	1	1.5	12300	29100	3800
95	110	130	35	1.1	1	13100	30700	3600
95	110	130	63	1.1	1	18900	48800	3600

(3)外徑尺寸 > 100mm以上者,需經濟批量訂購生產。
The out dimensions > 100mm are produced by order.

(4)NKIS 系列產品,需經濟批量訂購生產。
NKIS series are produced by order.