



Automatic Tapping Machine

Pitch Gear Auto Tapping Machine
Lead Screw Auto Tapping Machine



T-50 Max.Tapping Capacity : M10

Specification	T-50
Max. Tapping Capacity	M10
Spindle Taper	JT2
Spindle Travel	45mm
Spindle Speed	50HZ 420.760.1340 60HZ 500.900.1600
Swing	360mm
VP-down Travel of the Head	280mm
Column Diameter	Ø52mm
Diameter of working surface	260*240mm
Base Diameter	340*500mm
Diameter of spindle to Base	380mm
Motor HP	1HP
Overall Height	930mm
Gross weight	150kg



· Pitch Gear Auto Tapping Machine

T-50A Max.Tapping Capacity : M10



Specification	T-50A
Max. Tapping Capacity	M10
Spindle Taper	JT2
Spindle Travel	45mm
Spindle Speed	50HZ 420.760.1340 60HZ 500.900.1600
Swing	360mm
Column Diameter	Ø80mm
Table Diameter	Ø320mm
Base Diameter	330x510mm
Max.Distance of spindle to Table	350mm
Distance of spindle to pase	600mm
Motor HP	1HP
Overall Height	1100mm
Gross weight	200kg

• Pitch Gear Automatic Tapping Machine



T-50B Max.Tapping Capacity : M10

Specification	T-50B
Max. Tapping Capacity	M8
Spindle Taper	JT2
Spindle Travel	45mm
Spindle Speed	50HZ 420.760.1340 60HZ 500.900.1600
Swing	360mm
VP-down Travel of the Head	280mm
Table Diameter	650x800x760mm
Column Diameter	Ø52mm
Diameter of spindle to Base	380mm
Motor HP	1HP
Overall Height	1720mm
Gross weight	230kg



• Pitch Gear Automatic Tapping Machine

T-80 Max.Tapping Capacity : M16



Specification	T-80
Max. Tapping Capacity	M16
Spindle Taper	MT2
Spindle Travel	65mm
Spindle Speed	50HZ 155.285.515 60HZ 190.340.620
Swing	460mm
VP-down Travel of the Head	340mm
Column Diameter	Ø85mm
Diameter of working surface	280x250mm
Base Diameter	390x580mm
Distance of spindle to Base	470mm
Motor HP	2HP
Overall Height	1130mm
Gross weight	320kg

T-80A Max.Tapping Capacity : M16

Specification	T-80A
Max. Tapping Capacity	M16
Spindle Taper	MT2
Spindle Travel	65mm
Spindle Speed	50HZ 155.285.515 60HZ 190.340.620
Swing	460mm
Column Diameter	Ø102mm
Table Diameter	Ø420mm
Base Diameter	390x580mm
Max Distance Of Spindle To Table	530mm
Diameter of spindle to Base	840mm
Motor HP	2HP
Overall Height	1500mm
Gross weight	370kg



· Pitch Gear Automatic Tapping Machine

T-80B Max.Tapping Capacity : M16



Specification	T-80B
Max.Tapping Capacity	M16
Spindle Taper	MT2
Spindle Travel	65mm
Spindle Speed	50HZ 155.285.515 60HZ 190.340.620
Swing	460mm
VP-down Travel of the Head	340mm
Table Diameter	800x1000x760mm
Column Diameter	Ø85mm
Max.Distance of spindle to Table	470mm
Motor HP	2HP
Overall Height	1920mm
Gross weight	420kg

Lead-Screw Automatic Tapping Machine



T-360 Max.Tapping Capacity : M12

Specification	T-360
Max.Tapping Capacity	M12
Spindle Taper	MT2
Spindle Travel	100mm
Spindle Speed / 3S	600.1000.1500
Swing	360mm
Column Diameter	Ø80mm
Table Diameter	Ø320mm
Base Diameter	330*510mm
Distance from spindle to Table	400mm
Distance from spindle to Base	600mm
Motor HP	1HP
Overall Height	1150mm
weight	100kg

T-650 Max.Tapping Capacity : M20

Specification	T-650
Max.Tapping Capacity	M20
Spindle Taper	MT3
Spindle Travel	140mm
Spindle Speed / 3S	100.200.300
Variable Speed	330-1330
Swing	460mm
Column Diameter	Ø102mm
Table Diameter	Ø420mm
Base Diameter	410*600mm
Distance from spindle to Table	630mm
Distance from spindle to Base	930mm
Motor HP	2HP
Overall Height	1700mm
weight	220kg



**T-120 Max.Tapping Capacity : M20**

Specification	T-120
Max.Tapping Capacity	M20
Spindle Taper	MT3
Spindle Travel	120mm
Spindle Speed / 3S	100.200.300
Variable Speed	330-1330mm
Swing	460mm
Table Diameter	600*800mm
Column Diameter	Ø102mm
Distance from spindle to Table	350-700mm
Motor HP	2HP
Overall Height	2100mm
weight	600kg

T-140 Max.Tapping Capacity : M30

Specification	T-140
Max.Tapping Capacity	M30
Spindle Taper	MT4
Spindle Travel	150mm
Spindle Speed / 3S	100.200.300
Variable Speed	330-1330mm
Swing	520mm
Table Diameter	600*800mm
Column Diameter	Ø115mm
Distance from spindle to Table	350-700mm
Motor HP	3HP
Overall Height	2100mm
weight	700kg



· Accessories



Key Chuck



Keyless Chuck



Tapping Chuck



· Tapping Chuck

Standard Type



Size	Tapping Capacity
ST-MT1	M3-M8(U1/4-U5/16)
ST-MT2	M3-M14(U1/4-U7/16)
ST-MT3	M8-M22(U3/8-U7/8)
ST-MT4	M16-M38(U5/8-U13/8)

Radial Parallel Float Type



Size	Tapping Capacity	Float Range
FT-MT1	M3-M8(U1/4-U5/16)	0.25mm
FT-MT2	M3-M14(U1/4-U7/16)	0.5mm
FT-MT3	M8-M22(U3/8-U7/8)	1mm
FT-MT4	M16-M38(U5/8-U13/8)	1.5mm

Length Compensation Type



Size	Tapping Capacity	Flex Equalize Extend	Quantity Shrink
LT-MT1	M3-M8(U1/4-U5/16)	15mm	15mm
LT-MT2	M3-M14(U1/4-U7/16)	20mm	20mm
LT-MT3	M8-M22(U3/8-U7/8)	20mm	20mm
LT-MT4	M16-M38(U5/8-U13/8)	20mm	20mm

Radial Parallel Float With Length Compensation Type



Size	Tapping Capacity	Float	Flex Equalize Extend	Quantity Shrink
FLT-MT1	M3-M8(U1/4-U5/16)	0.25mm	20mm	15mm
FLT-MT2	M3-M14(U1/4-U7/16)	0.5mm	20mm	20mm
FLT-MT3	M8-M22(U3/8-U7/8)	1mm	20mm	20mm
FLT-MT4	M16-M38(U5/8-U13/8)	1.5mm	20mm	20mm

Tapping Adapter Standard



Size	Tapping Capacity
TC-0	M3-M8(U1/4-U5/16)
TC-1	M3-M14(U1/4-U7/16)
TC-2	M8-M22(U3/8-U7/8)
TC-3	M16-M38(U5/8-U13/8)

Tapping Adapter With Safety Clutch



Size	Tapping Capacity
TCS-0	M3-M8(U1/4-U5/16)
TCS-1	M3-M14(U1/4-U7/16)
TCS-2	M8-M22(U3/8-U7/8)
TCS-3	M16-M38(U5/8-U13/8)



LAING LIH MACHINE CO., LTD.

No. 247, Yasiou Rd., Daya Dist., Taichung City 428, Taiwan

TEL: 886-4-2560-1100

FAX: 886-4-2560-1012

E-mail: ktk.kaiwen@msa.hinet.net

▼ 掃描看更多 ▼



<http://www.ktk.com.tw>
<http://www.ktk-machinery.com>



Automatic Tapping Machine

Pitch Gear Auto Tapping Machine
Lead Screw Auto Tapping Machine



