

潤滑循環系統
Lubricating Circulation System



提供您最為合適的選擇
PROVIDE THE BEST CHOICE FOR YOU



產品介紹

省成本	省電、免冷媒、免水塔、免壓縮機、維修保養，簡易方便
標準化	品質穩定、使用保養簡易、縮短交期、迅速出貨
客製化	替您量身打造心目中的理想樣式
全檢試車	提高品質穩定性，在使用上更加放心
鋁基複合材	耐高壓、降溫快、輕巧、堅固、安全
板金雷射切割	設計精準、美觀
板金酸洗烤漆	可延長使用年限

Product Introduction

Cost Saving	Energy saving, No refrigerant, compressor, water tower, and the maintenance is simple and convenient
Aluminum	Can withstand high pressure, cooling rate is fast, light weight, strong and safe.
Standardization	Quality Stability, Easy to use and Maintenance, Shorten delivery period, rapid shipment
Customization	For you to create the ideal style of mind
Sheet metal pickling paint	Can prolong the service life
Sheet metal laser cutting	More beautiful and more accurate
Full test run	To improve quality stability, in the use of more assured



規格表 Specifications

規格 Specifications	冷卻能力 (kcal/h) Cooling Capacity	尺寸(mm±2) Size L*W*H	工作壓力(kg) Working pressure	流量 (L/min) Flow	出入口大小及螺紋 In & Out	
JDRC-P-0.25HP	1500	530*230*500	5	4	03 PT	
JDRC-20-03-18-S4	2200	420*200*340		6		
JDRC-20-03-18-F	2200	360*400*580				
JAOC-P-0.25HP-AOC-2003	1400	400*325*450		5	12	04 PT
JAOC-P-0.25HP-AOC-2003-AE						
JAOC-P-2003-CB+PS	2500	600*300*580			130	G1"
JAOC-2024-S4-CF	9000	600*650*550				
JAOC-2030-S4-CF	15000	600*650*550				



散熱風扇規格表 Specifications

JM	120	AP	22		標配		
系列號 Serial No.	尺寸 Size	外殼 Housing	電壓 Voltage		速度 Speed	軸承 Bearing type	接電方式 Connect Type
	120	鋁殼黑色 Aluminum Painted Black	11	AC 110	高速 High Speed	滾珠軸承 Ball Bearing	出線 Lead Wire
	172			AC 220			
	180		22	AC 220			
	205			Others			
	254		Others				
	Others			Others			



JANG MAW